



# CLAY PLANET

## Safety Data Sheet

SDS prepared by Jon Dunlavy 6/1/2015

GHS – United States

### Section 1. Identification

<b>Product Names</b>	<b>Lead-free Glazes With Copper:</b> <b>#2, 5, 9, 10, 14, 25, 143, 145, 206, 261, 263, 304, 305, 352, 423, 425, 430, 432, 433, 435, 437, 439, 440, 445, 503, 504, 509, 510, 512, 751, 4513, 4522, 4530, 4548, 4550, 4551, 4554, 4555, 4557, 4558, 4559, 4563</b>
<b>Synonym</b>	Ceramic Glaze – Water based, liquid, Cone 05 and 5 Glazes
<b>Supplier/ Manufacturer</b>	Clay Planet 1775 Russell Ave Santa Cara, CA 95054 USA 408-295-3352 phone 408-295-8717 fax 800-443-2529 toll-free <a href="mailto:info@clay-planet.com">info@clay-planet.com</a>
<b>Emergency Phone Number</b>	911
<b>Product Use</b>	Ceramic Sculpture and Pottery Surface coating
<b>Restrictions on use</b>	Not recommended for use in grades K-6. Not for spray application.

### Section 2. Hazards Identification

<b>OSHA/HCS status</b>	This wet mixture, <b>only when in dry powder form or if sprayed</b> , is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)
<b>Classification of the</b>	<b>OSHA - CARCINOGENICITY</b> (Inhalation) - Category 1A
<b>Substance or mixture</b>	(See section 16 for OSHA, IARC, and NTP carcinogen listings) <b>OSHA/HCS - SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure)</b> (respiratory tract) (inhalation) - Category 2
<b>Signal Word</b>	<b>Danger</b>
<b>Hazard Statement</b>	<b>WARNING!</b> Cancer Hazard. Contains quartz (crystalline silica) which can cause cancer. Risk of cancer depends upon duration and level of exposure to <b>dust</b> . Not an acute hazard. Prolonged inhalation of <b>dry glaze dust</b> may cause lung injury. Inhalation of high concentrations of <b>dry glaze dust</b> may cause mechanical irritation and discomfort of the (respiratory tract). Repeated exposure may cause chronic effects. Wear a N-95 face mask when cleaning up dry glaze dust. <b>WARNING!</b> May be harmful if swallowed. Inhalation of extremely high concentrations of copper compounds could cause pulmonary edema. Prolonged or repeated overexposure to copper salts may cause kidneys, liver and blood system effects. Prolonged or repeated contact of copper salts with skin may cause dermatitis. Avoid fumes from firing. <b>*Glaze in liquid form poses <u>no health risk</u>. Inhalation of dry glaze dust, fumes from firing or ingestion of glaze should be avoided.</b>

Lead-free Glazes With Copper:#2, 5, 9, 10, 14, 25, 143, 145, 206, 261, 263, 304, 305, 352, 423, 425, 430, 432, 433, 435, 437, 439, 440, 445, 503, 504, 509, 510, 512, 751, 4513, 4522, 4530, 4548, 4550, 4551, 4554, 4555, 4557, 4558, 4559, 4563



# CLAY PLANET

## Safety Data Sheet

SDS prepared by Jon Dunlavy 6/1/2015

GHS – United States

GHS label elements /  
Hazard pictograms



### Precautionary Statements

Avoid generating dust.  
Do not breath dust.  
Avoid skin contact.  
Do not take internally.  
Avoid fumes from firing.

### Unclassified Hazards

Slippery when wet.

### % of ingredients with unknown acute toxicity

None Known

Health Hazard	*	1
Fire Hazard		0
Reactivity		0
Personal Protection		E

\* Chronic Potential

## Hazardous Materials Identification System

### HAZARD INDEX

4 Severe Hazard    0 Minimal Hazard  
3 Serious Hazard    • An asterisk (\*) or other designation  
2 Moderate Hazard    corresponds to additional informa-  
1 Slight Hazard        tion on a data sheet or separate  
                                  chronic effects notification.

### PERSONAL PROTECTION INDEX

A	
B	+
C	+  +
D	+  +
E	+  +
F	+  +  +

### Section 3: Composition / Information on Ingredients

Substances: N/A

Mixtures: A propriety formula trade secret claim is made for this group of substantially similar mixtures.

Chemical	CAS Numbers	Ingredient % of Product Mixture (Glaze)	Chemical % of Ingredient
Quartz, (Crystalline Silica) SiO <sub>2</sub>	CAS # 14808-60-7	Kaolin Clays 2 – 15 Feldspars 0 – 18 Limestone (Whiting) 0 – 9 Frit 13 - 55 Zircopax Plus 0 – 6 Silica 0 – 16 Wollastonite 0-17	Kaolin Clays .45 Feldspars 7 - 13 Limestone (Whiting) .1 – 1 Frit 100 Zircopax Plus 0.1 - 0.5 Silica 98.7-99 Wollastonite 0.8-1.3
Kaolinite Al <sub>2</sub> O <sub>3</sub> .2SiO <sub>2</sub> .2H <sub>2</sub> O	CAS # 1332-58-7	Kaolin Clays 2 - 15	Kaolin Clays 95 - 98
Alumina Oxide Al <sub>2</sub> O <sub>3</sub>	CAS # 1344-28-1	Silica 0 – 16 Calcined Alumina 0- 3	Silica < 1.1 Calcined Alumina > 98
Mica (Na,K) <sub>2</sub> O.2Al <sub>2</sub> O <sub>3</sub> .6SiO <sub>2</sub> .2H <sub>2</sub> O	CAS # 12001-26-2	Kaolin Clays 2 - 15	Kaolin Clays 1-3
Calcium Carbonate CaO <sub>3</sub>	CAS# 1317-65-3	Limestone (Whiting) 0 – 9	Limestone (Whiting) 60 - 100
Titanium Dioxide TiO <sub>2</sub>	CAS # 13463-67-7	Titanium Dioxide 0-5 Silica 0-16	Titanium Dioxide 100 Silica < 0.1
Zirconium Silicate	CAS # 14940-68-2	Zircopax Plus 0 - 6	Zircopax Plus 95-100
Copper (cupric) Oxide CuO	CAS # 1317-38-0	Cupric oxide 0 - 5	Cupric oxide 60 - 100
Copper Carbonate CuCo <sub>3</sub>	CAS # 12069-69-1	Copper Carbonate 0 - 5	Copper Carbonate 98 - 100
Lithium Carbonate LiCO <sub>3</sub>	CAS # 554-13-2	Lithium Carbonate 0 - 7	Lithium Carbonate > 99
Gerstley Borate	CAS # 12007-56-6 and 1319-33-1	Gerstley Borate 0 - 12	Gerstley Borate < 100

Lead-free Glazes With Copper:#2, 5, 9, 10, 14, 25, 143, 145, 206, 261, 263, 304, 305, 352, 423, 425, 430, 432, 433, 435, 437, 439, 440, 445, 503, 504, 509, 510, 512, 751, 4513, 4522, 4530, 4548, 4550, 4551, 4554, 4555, 4557, 4558, 4559, 4563



# CLAY PLANET

## Safety Data Sheet

SDS prepared by Jon Dunlavy 6/1/2015

GHS – United States

### Section 3: Composition / Information on Ingredients

Feldspars	CAS # 68476-25-5	Feldspars	0 - 18	Feldspars	87 - 93
Wollastonite	CAS # 13983-17-0	wollastonite	0-17	Wollastonite	< 99
Trisodium Hexafluoroaluminate	CAS # 15096-52-3	Cryolite	0-9	Cryolite	> 95
Zinc Oxide	CAS # 1314-13-2	Zinc Oxide	0-3	Zinc Oxide	95-100
Sodium Carboxymethyl Cellulose	CAS # 9004-32-4	CMC Gum	0.7-0.8	CMC Gum	99-100
CTAC	CAS # 4080-31-3	Dowicil-75	0.03-0.05	Dowicil-75	64
Frit*	CAS # 65997-18-4	Frit	13-55	Frit	100
Ceramic Pigments**	Varies	Ceramic Pigments	0 - 40	Ceramic Pigments	0 - 40

\*Frit, CAS # 65997-18-4, is a complex mixture of materials, fused into a glassy substance, confining the materials into a non-migratory form.

\*\*Proprietary blends of pigments used that are not considered a hazard; follow guidelines set for silica as a precaution.

### Section 4: First-Aid Measures

#### Description of first-aid Measures:

<b>First-aid measures general</b>	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical attention.
<b>First-aid measures after inhalation</b>	Move victim to well ventilated area. If mechanical discomfort persists, seek medical attention.
<b>First-aid measures after skin contact</b>	Remove contaminated clothing. Wash affected area with soap and warm water. Obtain medical attention if irritation persists.
<b>First-aid measures after eye contact</b>	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking, or redness persists.
<b>First-aid measures after ingestion</b>	Rinse mouth. Give 200-300mL water to drink. Do NOT induce vomiting. If ingested, seek medical attention as a precaution.

#### Most Important Symptoms and Effects, both Acute and Delayed:

<b>Symptoms/injuries</b>	Causes damage to organs through prolonged or repeated exposure (inhalation) from dust, fumes from firing or from ingestion of glaze.
<b>Symptoms/injuries after inhalation</b>	May cause cancer by repeated inhalation. Dust or fumes from firing this product may cause irritation to the respiratory tract, lung inflammation, cough or chest pains.
<b>Symptoms/injuries after skin contact</b>	Prolonged contact with large amounts of copper salts may cause mechanical irritation and/or dermatitis. Exposure to copper salts may cause allergic reaction in sensitive individuals.
<b>Symptoms/injuries after eye contact</b>	Prolonged contact with large amounts of dust may cause mechanical irritation. Glaze is abrasive and may scratch eyes.
<b>Symptoms/injuries after ingestion</b>	If a large quantity has been ingested: intestinal blockage, gastrointestinal irritation, nausea, chills, or diarrhea.
<b>Chronic symptoms</b>	Repeated or prolonged exposure to respirable crystalline silica dust can cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal. Inhalation of extremely high concentrations of copper compounds could cause pulmonary edema. Prolonged or repeated overexposure to copper salts may cause kidneys, liver and blood system effects. Prolonged or repeated contact of copper salts with skin may cause dermatitis or allergic reactions in sensitive individuals. Avoid fumes from firing.

**If exposed or concerned, get medical advice and attention.**

Lead-free Glazes With Copper:#2, 5, 9, 10, 14, 25, 143, 145, 206, 261, 263, 304, 305, 352, 423, 425, 430, 432, 433, 435, 437, 439, 440, 445, 503, 504, 509, 510, 512, 751, 4513, 4522, 4530, 4548, 4550, 4551, 4554, 4555, 4557, 4558, 4559, 4563



# CLAY PLANET

## Safety Data Sheet

SDS prepared by Jon Dunlavy 6/1/2015

GHS – United States

### Section 5. Fire-Fighting Measures



#### National Fire Protection Association (U.S.A.)

<b>Suitable extinguishing media</b>	This product is not combustible. Use extinguishing media appropriate for surrounding fire.
<b>Unsuitable extinguishing media</b>	No restrictions on extinguishing media for this mixture.
<b>Special hazards arising from the substance or mixture</b>	This mixture is not flammable and does not support fire. The plastic bags and cardboard boxes containing the mixture are flammable.
<b>Hazardous thermal decomposition products</b>	This mixture does not contain hazardous decomposition products.
<b>Special protective actions for fire-fighters</b>	Product can become slippery when wet.
<b>Special protective equipment for fire-fighters</b>	Fire-fighters should wear appropriate protective equipment.

### Section 6. Accidental Release Measures

#### Use of personal precautions

Avoid inhalation of dry glaze dust.

**Wear a N-95 face mask when cleaning up dry glaze dust.**

Do not eat, drink or smoke while using this product.

#### Emergency procedures

There are no emergency procedures required for this mixture.

#### Methods and Materials for containment

Product comes in plastic pint or gallon jars.

Do not allow spills or wastewater to flow into sewer or waterway.

#### Clean up procedures

For dry dusts, use a vacuum to clean up spillage. For liquid spills, use suitable absorbent material and place in disposal containers. If appropriate, use gentle water spray to wet down and minimize dust generation. Spill area can be washed with water. Collect waste water for disposal. Place dry glaze dust in a sealed container.

**Wear a N-95 face mask when cleaning up dry glaze dust.**

### Section 7. Handling & Storage

#### Precautions for safe handling

Keep out of direct sunlight. Do not expose to freezing.

#### Recommendations on the conditions for safe storage

No special storage considerations, but keep in a dry, cool location.



# CLAY PLANET

## Safety Data Sheet

SDS prepared by Jon Dunlavy 6/1/2015

GHS – United States

### Section 8. Exposure Controls / Personal Protection

Chemical Name	CAS Numbers	Occupational Exposure Limits
Quartz, SiO <sub>2</sub> (Crystalline Silica)	CAS#14808-60-7	ACGIH TLV: TWA 0.025 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 10 mg/m <sup>3</sup> / divided by the value "%SiO <sub>2</sub> " + 2 (respirable) OSHA PEL: TWA 30 mg/m <sup>3</sup> / divided by the value "%SiO <sub>2</sub> " + 2 (total dust)
Kaolinite Al <sub>2</sub> O <sub>3</sub> .2SiO <sub>2</sub> .2H <sub>2</sub> O	CAS#1332-58-7	ACGIH TLV: TWA 2 mg/ m <sup>3</sup> (respirable) / particulate matter containing no asbestos and <1% crystalline silica (respirable) OSHA PEL: TWA 5 mg/m <sup>3</sup> (respirable) OSHA PEL: TWA 15 mg/m <sup>3</sup> (total)
Alumina Oxide Al <sub>2</sub> O <sub>3</sub>	CAS#1344-28-1	ACGIH TLV: TWA 10 mg/ m <sup>3</sup> for particulate matter containing no asbestos and < 1% crystalline silica OSHA PEL: TWA 5 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 15 mg/m <sup>3</sup> (total dust)
Calcium Carbonate CaCO <sub>3</sub>	CAS# 1317-65-3	ACGIH TLV: Not Established* OSHA PEL: TWA 5 mg/m <sup>3</sup> (respirable) OSHA PEL: TWA 15 mg/m <sup>3</sup> (total)
Mica (Na,K) <sub>2</sub> O.2Al <sub>2</sub> O <sub>3</sub> .6SiO <sub>2</sub> .2H <sub>2</sub> O	CAS# 12001-26-2	ACGIH TLV: TWA 3 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 3 mg/m <sup>3</sup> (respirable) OSHA PEL: TWA 20 mppcf See Appendix C (Mineral Dusts) which can be found in Section 16
Titanium Dioxide TiO <sub>2</sub>	CAS# 13463-67-7	ACGIH TLV: TWA 10 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 15 mg/m <sup>3</sup> (total dust)
Zirconium Silicate	CAS # 14940-68-2	ACGIH TLV: Not Established* OSHA PEL: Not Established*
Copper (Cupric) Oxide Copper Carbonate	CAS # 1317-38-0 CAS # 12069-69-1	ACGIH TLV: TWA 1 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 1 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 0.1 mg/m <sup>3</sup> (fume)
Lithium Carbonate	CAS # 554-13-2	ACGIH TLV: Not Established* OSHA PEL: TWA 5 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 15 mg/m <sup>3</sup> (total dust)
Gerstley Borate	CAS # 12007-56-6 And 1319-33-1	ACGIH TLV: TWA 2 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 5 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 15 mg/m <sup>3</sup> (total dust)
Feldspars	CAS # 68476-25-5	ACGIH TLV: Not Established* OSHA PEL: Not Established*
Wollastonite	CAS # 13983-17-0	ACGIH TLV: TWA 3 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 5 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 15 mg/m <sup>3</sup> (total dust)
Trisodium Hexafluoroaluminate	CAS # 15096-52-3	ACGIH TLV: TWA 2.5 mg/ m <sup>3</sup> (as F) OSHA PEL: TWA 2.5 mg/ m <sup>3</sup> (as F)
Zinc Oxide	CAS # 1314-13-2	ACGIH TLV: TWA 2 mg/ m <sup>3</sup> (respirable) OSHA PEL: TWA 5 mg/ m <sup>3</sup> (respirable and fume) OSHA PEL: TWA 15 mg/m <sup>3</sup> (total dust)
Sodium Carboxymethyl Cellulose	CAS # 9004-32-4	ACGIH TLV: Not Established* OSHA PEL: Not Established*
CTAC	CAS # 4080-31-3	ACGIH TLV: Not Established* OSHA PEL: Not Established*

Lead-free Glazes With Copper:#2, 5, 9, 10, 14, 25, 143, 145, 206, 261, 263, 304, 305, 352, 423, 425, 430, 432, 433, 435, 437, 439, 440, 445, 503, 504, 509, 510, 512, 751, 4513, 4522, 4530, 4548, 4550, 4551, 4554, 4555, 4557, 4558, 4559, 4563



# CLAY PLANET

## Safety Data Sheet

SDS prepared by Jon Dunlavy 6/1/2015

GHS – United States

### Section 8. Exposure Controls / Personal Protection

Frit	CAS # 65997-18-4	ACGIH TLV: Not Established* OSHA PEL: Not Established*
Ceramic Pigments	Varies	ACGIH TLV: Not Established* OSHA PEL: Not Established*

\*For values not established, follow guidelines set for silica as a precaution

#### Appropriate engineering controls

Glaze in liquid form poses no health risk and no inhalation risk (dust).

Once glaze has dried, there may be dust generated by cleaning and working processes.

In the event that dust is generated, use local exhaust ventilation or other engineering controls as required to maintain exposures below applicable occupational exposure limits (TLV).

Not recommended for spray application, but local exhaust system may be used as required to maintain exposures below applicable occupational exposure limits (TLV) while spraying.

#### Recommendations for personal protective measures

**Local Exhaust:** When dry sanding or grinding clay/glaze products, or during spray application of glaze, use sufficient local exhaust to reduce the level of respirable dust to the applicable standards set forth in Section III. See ACGIH "Industrial Ventilation, A Manual of Recommended Practice," latest edition.

**Respiratory Protection:** Dust is generated when working with dry glaze or during spray application. To minimize exposure to dust and/or crystalline silica, cutting or sanding dry clay/glaze products should be conducted with sufficient ventilation. Respirable dust and quartz levels should be monitored regularly. Dust and quartz levels in excess of appropriate exposure limits should be reduced by feasible engineering controls, including (but not limited to) wet sanding, wet suppression, ventilation, and process enclosure. When such controls are not feasible, NIOSH/MSHA approved respirators must be worn in accordance with a respiratory protection program which meets OSHA requirements as set forth at 29 CFR1910.134 and ANSI Z88.2-1080 "Practices for Respiratory Protection". **In most cases, a disposable N-95 Particulate Respirator is sufficient.**

**Eye Protection:** Use NIOSH/OSHA approved safety glasses with side shields. Face shields should also be used when dry sawing clay/glaze products. Wear tight fitting dust goggles when excessively (visible) dusty conditions are present or are anticipated. NIOSH recommends that contact lenses not be worn when working with crystalline silica dust.

**Skin Protection:** Use gloves and/or protective clothing if abrasion or allergic reactions are experienced.

**Work/Hygienic Practices:** Avoid creating and breathing dust. Wear NIOSH/MSHA approved dust mask when working in dusty conditions. (N-95) Food, beverages, and smoking materials should NOT be in the work area. Persons using ceramic materials should wash thoroughly before eating, drinking, smoking, or applying cosmetics.



Protective Clothing Pictograms

N-95 face mask



# CLAY PLANET

## Safety Data Sheet

SDS prepared by Jon Dunlavy 6/1/2015

GHS – United States

### Section 9. Physical & Chemical Properties

Physical State	Liquid glaze
Appearance	Colored, heavy liquid
Odor	Earthy
Odor Threshold	Not Applicable
pH	6 - 8
Solubility in Water	Miscible
Melting Point	> 982 °C (>1800°F)
Freezing Point	< 0 °C (<32°F)
Specific Gravity	1.3 - 1.8
Relative Density	10.8 - 15.0 lb/gal
Evaporation Rate	No data available
Boiling Point	100°C (212°F)
Flash Point	Not Applicable
Auto-Ignition Temperature	Not Applicable
Decomposition Temperature	Not Applicable
Flammability	Not Applicable
Vapor Pressure	Not Applicable
Vapor Density	Not Applicable
Explosive Limits	Not Applicable
Viscosity	Not Applicable
Partition Coefficient: n-octanol/water	Not Applicable

### Section 10: Stability & Reactivity

<b>Reactivity</b>	Hazardous reactions will not occur under normal conditions.
<b>Chemical stability</b>	Stable at standard temperature and pressure. No stabilizers required to maintain chemical stability.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization will not occur.
<b>Conditions to avoid</b>	None known.
<b>Incompatible materials</b>	None known
<b>Hazardous decomposition products</b>	Copper fumes from firing.

### Section 11: Toxicological Information

**Routes of Exposure** Inhalation of dry glaze dust, Ingestion

Descriptions of the delayed, immediate, or chronic effects from short- and long-term exposure	
<b>Inhalation</b>	Inhalation of high concentrations of dry glaze dust may cause mechanical irritation and discomfort. Repeated exposure may cause chronic effects.
<b>Eye Contact</b>	Not a primary eye irritant. May cause mechanical irritation.
<b>Skin Contact/Irritation</b>	May cause allergic reaction in sensitive individuals (copper). Not absorbed through skin.
<b>Sensitization</b>	Not a sensitizer.
<b>Ingestion</b>	May cause anemia, damage to kidneys and/or liver.

Lead-free Glazes With Copper:#2, 5, 9, 10, 14, 25, 143, 145, 206, 261, 263, 304, 305, 352, 423, 425, 430, 432, 433, 435, 437, 439, 440, 445, 503, 504, 509, 510, 512, 751, 4513, 4522, 4530, 4548, 4550, 4551, 4554, 4555, 4557, 4558, 4559, 4563



# CLAY PLANET

## Safety Data Sheet

SDS prepared by Jon Dunlavy 6/1/2015

GHS – United States

Chronic Effects	
<b>OSHA Carcinogen</b>	Lung cancer – Silica has been classified by OSHA as a human lung carcinogen. <b>Repeated or prolonged exposure</b> to respirable crystalline silica dust can cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal.
<b>Mutagenic Effects</b>	None Known
<b>Teratogenic Effects</b>	None Known
<b>Developmental Toxicity</b>	None Known
Effects of Silicosis	
Bronchitis/Chronic Obstructive Pulmonary Disorder. Tuberculosis – Silicosis makes an individual more susceptible to TB. Scleroderma – a disease affecting skin, blood vessels, joints and skeletal muscles. Possible renal disease.	<b>Symptoms of Silicosis</b> Shortness of breath; possible fever. Fatigue; loss of appetite. Chest pain; dry, nonproductive cough. Respiratory failure, which may eventually lead to death.
<b>Numerical Measures of toxicity</b>	None Known

### Section 12. Ecological Information (non-mandatory)

**Prevent from entering drains, sewers and waterways**

**Copper compounds may be hazardous to the environment and aquatic life.**

**Lithium and Zinc compounds may be hazardous to the environment and aquatic life if released in large quantities.**

### Section 13. Disposal Considerations (non-mandatory)

#### Personal Protection

Refer to Section 8: “Recommendations for Personal Protective Measures” when disposing of ceramic waste.

#### Appropriate disposal containers

Standard waste disposal containers – no specials requirements.

#### Appropriate disposal methods

Disposal of this product should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

The generation of waste should be avoided or minimized. Dispose of non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers.

#### Physical and chemical properties that may affect disposal

Dry glaze dust should be placed in a sealed container or in a manner that reduces or eliminates the release of the product. Liquid glaze should be placed in suitable container. Packaging should be recycled before disposal.

#### Sewage disposal

Do not dispose of into sinks or toilets. They will clog. Never dispose of this product into a sewer system.

#### Special precautions for landfills or incineration activities

There are no special precautions for disposal in a landfill. This product is non-combustible and is not suitable for incineration.





# CLAY PLANET

## Safety Data Sheet

SDS prepared by Jon Dunlavy 6/1/2015

GHS – United States

### Section 14. Transportation Information (non-mandatory)

Regulatory Information	UN Number	UN Proper Shipping Name	Transport Hazard Class	Packing Group Number	Bulk Transport Guidance	Special Precautions
DOT Classification	Not regulated	-	-	-	-	-
TDG Classification	Not regulated	-	-	-	-	-
ADR/RID Class	Not regulated	-	-	-	-	-
IMDG Class	Not regulated	-	-	-	-	-
IATA-DGR Class	Not regulated	-	-	-	-	-

### Section 15. Regulatory Information (non-mandatory)

<b>TSCA – Toxic Substances Control Act - EPA</b>	Quartz and other chemicals are listed in the TSCA Chemical Substance Inventory
<b>CONFORMS WITH ASTM D4236</b>	ASTM - American Society for Testing and Materials
<b>California Prop. 65</b>	<b>WARNING:</b> This product contains a chemical known to the State of California to cause cancer. (Prop. 65 - Calif. Health & Safety Code Section 2549 Et Seq.)

### Section 16. Other Information

#### OSHA, IARC, and NTP Carcinogen Classifications

Chemical with Carcinogen Potential	CAS#	OSHA	IARC	NTP
Quartz, (Crystalline Silica) SiO <sub>2</sub>	CAS # 14808-60-7	Yes	Yes - Group 1	Yes
Kaolinite	CAS # 1332-58-7	No	No - Group 3	No
Alumina Oxide	CAS # 1344-28-1	No	No - Group 3	No
Mica	CAS # 12001-26-2	No	No - Group 3	No
Calcium Carbonate	CAS # 1317-65-3	No	No - Group 3	No
Zirconium Silicate	CAS # 14940-68-2	No	No - Group 3	No
Copper (Cupric) Oxide	CAS # 1317-38-0	No	No - Group 3	No
Copper Carbonate	CAS # 12069-69-1	No	No - Group 3	No
Lithium Carbonate	CAS # 554-13-2	No	No - Group 3	No
Gerstley Borate	CAS # 12007-56-6 and 1319-33-1	No	No - Group 3	No
Feldspars	CAS # 68476-25-5	No	No - Group 3	No
Wollastonite	CAS # 13983-17-0	No	No - Group 3	No
Zinc Oxide	CAS # 1314-13-2	No	No - Group 3	No
Sodium Carboxymethyl Cellulose	CAS # 9004-32-4	No	No - Group 3	No
CTAC	CAS # 4080-31-3	No	No - Group 3	No
Trisodium Hexafluoroaluminate	CAS # 1509-52-3	No	No - Group 3	No
Titanium Dioxide TiO <sub>2</sub>	CAS # 13463-67-7	No	Yes – Group 2b	No
Frit	CAS # 65997-18-4	N/A	No – Group 3	N/A
Ceramic Pigments	Various; Follow guidelines for silica	N/A	N/A	N/A

Substances, mixtures and exposure circumstances in this list have been classified by the IARC as **Group 1: The agent (mixture) is carcinogenic to humans**. The exposure circumstance entails exposures that are carcinogenic to humans. This category is used when there is sufficient evidence of carcinogenicity in humans. Exceptionally, an agent (mixture) may be placed in this category when evidence of carcinogenicity in humans is less than sufficient but there is sufficient evidence of carcinogenicity in experimental animals and strong evidence in exposed humans that the agent (mixture) acts through a relevant mechanism of carcinogenicity.

Lead-free Glazes With Copper: #2, 5, 9, 10, 14, 25, 143, 145, 206, 261, 263, 304, 305, 352, 423, 425, 430, 432, 433, 435, 437, 439, 440, 445, 503, 504, 509, 510, 512, 751, 4513, 4522, 4530, 4548, 4550, 4551, 4554, 4555, 4557, 4558, 4559, 4563



# CLAY PLANET

## Safety Data Sheet

SDS prepared by Jon Dunlavy 6/1/2015

GHS – United States

The agents in this list have been classified in **Group 2A (probable carcinogens)**<sup>(1)</sup> by the **IARC (International Agency for Research on Cancer)**. The term "agent" encompasses both substances and exposure circumstances that pose a risk. This designation is applied when there is *limited evidence* of **carcinogenicity** in humans as well as *sufficient evidence* of carcinogenicity in **experimental animals**. In some cases, an agent may be classified in this group when there is *inadequate evidence* of carcinogenicity in humans along with *sufficient evidence* of carcinogenicity in experimental animals and *strong evidence* that the carcinogenesis is mediated by a mechanism that also operates in humans. Exceptionally, an agent may be classified in this group solely on the basis of *limited evidence* of carcinogenicity in humans.

Substances, mixtures and exposure circumstances in this list have been classified by the **International Agency for Research on Cancer (IARC)** as **Group 2B: The agent (mixture) is possibly carcinogenic to humans**. The exposure circumstance entails exposures that are *possibly carcinogenic to humans*. This category is used for agents, mixtures and exposure circumstances for which there is limited evidence of carcinogenicity in humans and less than sufficient evidence of carcinogenicity in experimental animals. It may also be used when there is inadequate evidence of carcinogenicity in humans but there is sufficient evidence of carcinogenicity in experimental animals. In some instances, an agent, mixture or exposure circumstance for which there is inadequate evidence of carcinogenicity in humans but limited evidence of carcinogenicity in experimental animals together with supporting evidence from other relevant data may be placed in this group. Further details can be found in the **preamble to the IARC Monograph**.

Substances, mixtures and exposure circumstances in this list have been classified by the **IARC** as **Group 3: The agent (mixture or exposure circumstance) is not classifiable as to its carcinogenicity to humans**. This category is used most commonly for agents, mixtures and exposure circumstances for which the evidence of carcinogenicity is inadequate in humans and inadequate or limited in experimental animals. Exceptionally, agents (mixtures) for which the evidence of carcinogenicity is inadequate in humans but sufficient in experimental animals may be placed in this category when there is strong evidence that the mechanism of carcinogenicity in experimental animals does not operate in humans. Agents, mixtures and exposure circumstances that do not fall into any other group are also placed in this category. Further details can be found in the **IARC Monographs**.

### Appendix C – Supplementary Exposure Limits

#### Mineral Dusts

OSHA PELs for "mineral dusts" listed below are from Table Z-3 of 29 CFR 1910.1000. The OSHA PEL (8-hour TWA) for crystalline silica (as respirable quartz) is either 250 mppcf divided by the value "%SiO<sub>2</sub> + 5" or 10 mg/m<sup>3</sup> divided by the value "%SiO<sub>2</sub> + 2." The OSHA PEL (8-hour TWA) for crystalline silica (as total quartz) is 30 mg/m<sup>3</sup> divided by the value "%SiO<sub>2</sub> + 2." The OSHA PELs (8-hour TWAs) for cristobalite and tridymite are ½ the values calculated above using the count or mass formulae for quartz.

The OSHA PEL (8-hour TWA) for amorphous silica (including diatomaceous earth) is either 80 mg/m<sup>3</sup> divided by the value "%SiO<sub>2</sub>," or 20 mppcf.

The OSHA PELs (8-hour TWAs) for talc (not containing asbestos), mica, and soapstone are 20 mppcf. The PELs for talc (not containing asbestos), mica, and soapstone, are applicable if the material contains less than 1% crystalline silica.

### Section 16. Other Information

#### Definitions

OSHA means Occupational Safety & Health Administration

IARC means **International Agency for Research on Cancer**

NTP means National Toxicology Program

HCS means Hazardous Communication Standard

TLV means Threshold Limit Value - American Conference of Governmental Industrial Hygienists (ACGIH)

PEL means OSHA Permissible Exposure Limit

TWA means Time Weighted Average (average exposure on the basis of an 8h/day, 40h/week work schedule)

CAS means Chemical Abstract Service

ASTM means American System of Testing and Materials

Lead-free Glazes With Copper:#2, 5, 9, 10, 14, 25, 143, 145, 206, 261, 263, 304, 305, 352, 423, 425, 430, 432, 433, 435, 437, 439, 440, 445, 503, 504, 509, 510, 512, 751, 4513, 4522, 4530, 4548, 4550, 4551, 4554, 4555, 4557, 4558, 4559, 4563



# CLAY PLANET

## Safety Data Sheet

SDS prepared by Jon Dunlavy 6/1/2015

GHS – United States

This SDS is in compliance with The Globally Harmonized System of Classification and Labeling of Chemicals (GHS). This data sheet is subject to change without notice.

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.